


Standalone Digital Signage Chassis 12" LCD Media Player, the compact size and ultimate space saving with efficient computing solution. The single zone is the suggestion for the compact size LCD media player.



Features

- Entire disk looping playback (In order to content's alphabetical)
- Video formats: 3gp / flv / mov / webm / AVI / DIVX & MPEG 1/2/4"
- Image formats: jpg, png, bmp, tiff
- Audio formats: MP3, WMA, WAV
- Performance: 1080P (one of multi-zone) / 720P / 480P
- Support scrolling text
- Sliding Photo
- Scheduling by weekly, segments to play specified contents

Panel	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating
	Aspect Ratio / Size	4 : 3 / 12.1" viewable diagonal area
	Active Area / Pixel Pitch	246.0(H) x 184.5(V) mm / 0.3075(H) x 0.3075(V) mm
	Native Resolution / Colors	800(H) x 600(V) / 262 K
	Brightness / Contrast	1000 cd/m ² (typ) / 600 : 1
	Response Time	≤ 35 ms
	Viewing Angle (typical)	H. 140° (- 70° ~ + 70°) , V. 120°(- 60° ~ + 60°)
	Light Source	LED backlight, Long life, 35,000 hrs (typ)
Function	Performance	1080P (one of multi-zone) / 720P / 480P
	Video Codecs	3gp / flv / mov / webm / AVI / DIVX & MPEG 1/2/4"
	Image Codecs	jpg, png, bmp, tiff
	Audio Codecs	MP3, WMA, WAV
	Scheduling	Scheduling by weekly, segments to play specified contents
	Multi-Zone	Adjustable Multi-Zone
	Scrolling Text	Text feed from remote server
	Rotation	Yes, Portrait / Landscape
	Sliding Photo	Yes
	Grouping	N / A
Optional	Touch	RT / PCT /IR
	Motion Sensor	Yes
I/O Port	Video Out	HDMI
	USB	Content update via USB
	SD	Storage
Power	Power Input	12V DC-IN (Lockable connector)
	Power Consumption	22W (typ.)
Environmental	Operating Temperature	0~ 50°C
	Operating Humidity	Relative humidity 10% ~ 90% @40°C, Non-condensing