

L1988V

Specification



Features

- Input sources switch by hot key
- Designed for global application, auto detect NTSC, PAL and SECAM video system
- Option : Looping function (AV2, AV2-Looping)
- Option : 3D platform
3D Comb filter with concurrent 3D noise reduction for high quality motion adaptive
4H Comb filter for chroma and luma separation to achieve best video quality

Panel	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating		
	Aspect Ratio / Size	4 : 3 / 19" viewable diagonal area		
	Active Area / Pixel Pitch	376.3(H) x 301.1(V) mm / 0.294(H) x 0.294(V) mm		
	Native Resolution / Colors	1280(H) x 1024(V) / 16.7 Million		
	Brightness / Contrast	300 cd/m ² (typ) / 800 : 1		
	Response Time	≤ 5 ms		
	Viewing Angle (typical)	H. 160° (- 80° ~ + 80°) , V. 160°(- 80° ~ + 80°)		
	Light Source	CCFL , Long life, 50,000 hrs (typ)		
Input Sources	Video System	NTSC / PAL / SECAM supported (Auto detecting)		
	PC System	Signal	Analog RGB (0.7/1.0 V _{p-p} , 75 ohms)	
		Sync	Separate Sync, Composite Sync, Sync On Green	
		Frequency	F _h : 30 - 82Khz , F _v : 50 -75Hz	
Audio System	2W speaker x 2			
Input Terminals	1 x VGA (15 Pin Female D-Sub) , 1 x PC Audio (Stereo Headphone Jack) , 1 x DC Power Plug			
	1 x S-Video , 1 x CVBS(BNC) , 2 x Audio(RCA, Audio-R + Audio-L)			
Convenient Features	Auto Calibration , Back Light Adjustment , Plug&Play (VESA DDC/CI, DDC 2B)			
	OSD Multi-Languages , Wall Mount Ready (VESA 100 x 100 mm)			
Power	External AC-to-12VDC power adapter with universal / Auto-Sensing, AC 90 to 260V, 50 / 60 Hz			
Power Consumption	Operation / Power Saving	32 watt , < 2 watt (Support DPMS)		
Operating Condition	Temperature / Humidity	0°C ~ 50°C (32°F ~ 122°F) , 10% ~ 90% (no condensation)		
Storage Condition	Temperature / Humidity	- 20°C ~ 60°C (- 4°F ~ 140°F) , 10% ~ 90% (no condensation)		
Certification	FCC , CE			
Dimensions	Physical	With Base(W x H x D) : 412.3 x 395.2 x 183.0 mm		
		Without Base(W x H x D) : 412.3 x 350.7 x 49.6 mm		
	Carton	W x H x D = 470 x 445 x 142 mm		
Weight	N.W. / G.W.	6.0 Kgs / 7.0 Kgs		
Container Loaded	20ft / 40ft / 40ft HQ	816 / 1632 / NA (Sets , By pallet)		

Options	Video / TV	Enhanced Panel
	AV2	Panel with LED backlight
	AV2-Looping	High brightness panel
		Wide Temperature
		Sun Light Readable

Winsonic[®]

Winsonic Electronics CO.,LTD. TEL:886-3-3704789 FAX:886-3-3704722 E-mail:sales@ewinsonic.com
No.290-1 Wun-Jhong Rd. Taoyuan City, Taoyuan Taiwan R.O.C

Online Download

www.ewinsonic.com