

# VH-PCH10452-XNA0L3-CB0M05 Specification

Fanless Vehicle Chassis Panel PC, 10.4" LCD monitor, 1024 x 768, LED 1000 nits, wide temperature and wide view angle, Intel® Celeron J1900



## Features

- Modularize mechanical design provides flexible product configuration and easy maintenance
- Optional build-in touch screen for interactive application
- Intel® Atom Baytrail-M/D Chipset
- Intel® Celeron J1900
- Single Channel DDR3L 1333 MHz SDRAM
- 1 x HDMI, 1 x COM, 2 x USB, 2 x LAN

Panel	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating
	Aspect Ratio / Size	4 : 3 / 10.4" viewable diagonal area
	Active Area / Pixel Pitch	210.4(H) x 157.8(V) mm / 0.2055(H) x 0.2055(V) mm
	Native Resolution / Colors	1024(H) x 768(V) / 16.2 M
	Brightness / Contrast	1000 cd/m <sup>2</sup> (typ) / 1000 : 1
	Response Time	≤ 25 ms
	Viewing Angle (typical)	H. 178° (- 89° ~ + 89°) , V. 178°(- 89° ~ + 89°)
	Light Source	LED backlight, Long life, 35,000 hrs (typ)
System	CPU	Intel® Celeron J1900
	BIOS	AMI
	System / Graphic Chipset	Intel® Atom Baytrail-M/D Chipset
	System Memory	Single Channel DDR3L 1333 MHz SDRAM
	HDD	2 x SATA
	I/O port	1 x HDMI
		2 x USB 3.0
1 x COM (RS232)		
2 x LAN		
Expension	1 x Mini PCI-e	
Power	Power Input	12V DC-IN (Lockable connector)
	Power Consumption	30 Watt, <1 Watt
Operating Condition	Temperature / Humidity	-30°C ~ 70°C (-22°F ~ 158°F) , 10% ~ 90% (no condensation)
Dimensions	Physical	Please refer to Drawing
	Carton	W x H x D = TBD

Options	Touch	Video / TV	Enhanced Panel	Others
	Resistive touch	SV + AV	Panel with LED backlight	Digital Signage(Stand alone)
	Capacitive touch	SV + AV + AV_Looping	High brightness panel	Networking Digital Signage
	SAW touch	SV + AV + TV	Wide Temperature	Motion Sensor
	Infrared touch		Sunlight Readable	Light Sensor
	Protected glass			Auto-Dimming