

CD860-V

Specification



Features

- Display 2 x 20 characters
- Adjustable display angle and height
- Large and easy to read display
- Pass-through function to save cable connection
- Compatible with ESC/POS command
- RS-232 interface at 9600 baud rate
- Telescopic pole 270mm~440mm or optional fixed pole 300mm or 400mm.

Tube Display	Customer Display	Vacuum Fluorescent Display
	Display Pattern	5 x 7 dot matrix
	Brightness	700 cd/m ²
	Character Type	96 alphanumeric & 13 international characters
	Command Set	ESC/POS
	Character Size	6.4W x 9.2H mm
	Character Number	2 x 20
Electrical	Power Source	DC 9V~12V (RS-232)
	Power Consumption	4.5 Watts (RS-232)
	Central Control Unit	CPU 8032 ROM 64K flash ROM 32K SRAM
	Speed	29Mhz
Physical	Dimensions (Panel)	224W x 45D x 83H mm
	Dimensions (Support)	Telescopic pole 270~440mm or optional fixed pole 300m or 400mm
	Dimensions (Base)	187W x 84D x 22H mm
	Tilt Angle	Max. 53°
	Rotation Angle	Max. 360°
	Weight	0.8Kg
	Interface	RS-232
	Color	Black or beige
Environmental	Operating Temperature	0°C~40°C(32°F~104°F)
	Storage Temperature	-10°C~50°C(14°F~122°F)
	Relative Humidity	0%~90% RH

Winsonic®

Winsonic Electronics CO.,LTD. TEL:886-3-3704789 FAX:886-3-3704722 E-mail:sales@ewinsonic.com
No.290-1 Wun-Jhong Rd. Taoyuan City, Taoyuan Taiwan R.O.C

Online Download

www.ewinsonic.com