



Winsonic[®]

Specification for Inverter 2P

Application : 100W (46V 1.1A x2)

This specification is applied to LED inverter unit for LCD backlight

Feature:

Over Voltage Protection

Destiny Current Protection

Under VoltageLock Out

MAXIMUM RATINGS*

Symbol	Parameter	Value	Unit
Vin	Supply Voltage	24V	Vdc
I _{max}	Input Current	4.2A	Adc
P _{max}	Output power	100.00	Watts
Top	Operating Temperature	0 ~ 60	C°
Tst	Storage Temperature	-20 ~ 70	C°

LED Rail Output

Mating Connector CN2/CN3

Pin No.	Signal
1	+Vout :46V 1.1A
2	-Vout

LED Rail Output

Mating Connector CN4/CN5

Pin No.	Signal
1	+Vout : 46V 1.1A
2	-Vout

CONNECTORS

Voltage Input

Mating Connector CN1

Pin No.	Signal
1	24VDC
2	GND
3	Internal PWM (DC Power Control Duty, 0~5V);(0V, 100% Duty) for
4	GND
5	ON/OFF(2.5~5V ON, 0~0.8V OFF)

RECOMMENDED OPERATING VALUES

Symbol	Parameter	Typical Value	Unit
Vin	Supply Voltage	24V	Vdc
L _{high}	Logic Input High	2.5 ~ 5	Vdc
L _{low}	Logic Input Low	0~ 0.8	Vdc
Din	Dimming Potentiometer	0 ~ 5.0	Vdc



