

NVR100 Series



NVR Software Overview

Our NVR supports 97 well-known brands and over 2100 IP camera models. PC based video recording server. It can display live video and configure the system. NUUO DVR has an intuitive design which can be learned very quickly.

Playback system makes browsing records smarter and faster through our intelligent search. Save video recompresses the image into ASF/AVI format. Video enhancement tool can be used to sharpen, brighten or even grey scale the images. Varies logs make keeps a record of all the events.

Remote live viewer client supports 64* channels per monitor and can view up to 128 cameras in dual monitor systems. Remote live viewer can display live video from multiple. i-Phone / i-Pad/ Android are ready.

Model Name	NVR119001	NVR119002	NVR119003	NVR119004
Channels	Up to 16		Up to 32	
Display Screen	19"			
Touch Method				
MotherBoard	CB0M02-D525	CB0J02-D525	CB0J06-QM57	CB0J06-QM57
CPU	Atom™ D525	Atom™ D525	Intel I5	Intel I7
RAM	2GB	4GB	8GB	8GB
Ethernet Port (on motherboard)	2 x 10/100/1000Mbps			
I/O Ports	1xVGA, 1xCOM, 2xUSB, 2xLAN	2 x VGA, 1 x Audio 2 x LAN, 4 x COM, 6 x USB, 2 x SATA	1xVGA, 2xCOM, 2xLAN, 6xSATA II, 3xAudio, 1xDVI, 6xUSB	
OS	Windows 7			
Number of Hard Drives	2 x SATA II			
Speak	3W			
PoE Output Power	30W per port			
Ethernet of PoE	Auto MDI, 10/100, Full/Half auto-detect			
PoE Power Budget	Total 60W			
PoE ports	4 Ports			
PoE Standard	IEEE802.3at			
PoE Power Supply type	End Span, PSE			
Power Pin of PoE	1/2 (+), 3/6 (-)			
Compression	H.264, MPEG-4, MJPEG, MxPEG (depends on IP camera)			
Remote Client	Remote Live Viewer (Software), Remote Live Viewer (Web), iViewer (Mobile App)			
Remote Client OS	Windows 2008, Windows XP (32-bit), Win7 (32 and 64-bit), IOS, Android			
Mobile Client Platform	iPhone, iPad, Android			
Digital PTZ	Supported in Live view and Playback			
Multiple Show	Supported in Live view			
Recording Type	Continuous record, record by digital input, motion record, event recording, boosting recording, record by schedule, manual record			
Auto Recycling Recording	Auto recycling when storage disk is full			
Supported Languages	Bulgarian, Chinese (Simplified), Chinese (Traditional), Czech, Danish, English, Farsi, Finnish, French, German, Hebrew, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese (Brazil), Portuguese (Portugal), Romanian, Russian, Serbian, Slovak, Spanish, Swedish, Thai, Turkish			
IP Camera Brand(s)	ACTi, Arecont, ARM, ATLANTIS, AXIS, BASLER, Bosch, Brickcom, CAMTRON, CISCO,			

Winsonic[®]
Winsonic Electronics CO.,LTD.

www.ewinsonic.com