

Zero Bezel Chassis Mount, 10.1" LCD monitor, 1280 x 800, LED 1000 nits, wide view angle and wide temperature
Intel® 7th/ 6th Gen (Kabylake-S/Skylake-S) Core™ Processors



Features

- Modularize mechanical design provides flexible product configuration and easy maintenance
- Optional build-in touch screen for interactive application
- Intel® 7th/ 6th Gen (Kabylake-S/Skylake-S) Core™ Processors
- 2 x 260-pin SO-DIMM up to 32GB DDR4 2133 MHz (16GB per DIMM)
- 2 x Display Port, 4 x USB 3.0, 2 x LAN

Panel	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating
	Aspect Ratio / Size	Wide / 10.1" viewable diagonal area
	Active Area / Pixel Pitch	216.96(H) x 135.6(V) mm / 0.1695(H) x 0.1695(V) mm
	Native Resolution / Colors	1280(H) x 800(V) / 262 K
	Brightness / Contrast	1000 cd/m ² (typ) / 800 : 1
	Response Time	≤ 16 ms
	Viewing Angle (typical)	H. 160° (- 80° ~ + 80°) , V. 160° (- 80° ~ + 80°)
	Light Source	LED backlight, Long life, 35,000 hrs (typ)
System	CPU	SBC-330P (i7-6600U, QC, 2.60GHz, 15W)
	BIOS	SBC-330M (i5-6300U, QC, 2.40GHz, 15W)
	System / Graphic Chipset	MCP
	System Memory	2 x 260-pin SO-DIMM up to 32GB DDR4 2133 MHz (16GB per DIMM)
	HDD	2 x SATA
	I/O port	2 x Display port
		4 x USB 3.0
2 x LAN		
Expension	N/A	
Power	Power Input	12V DC-IN (Lockable connector)
	Power Consumption	51 Watt, <1 Watt
Operating Condition	Temperature / Humidity	-20°C ~ 60°C (- 4°F ~ 140°F) , 10% ~ 90% (no condensation)
Dimensions	Physical	Please refer to Drawing
	Carton	W x H x D = TBD

Options	Touch	Video / TV	Enhanced Panel	Others
	Resistive touch	SV + AV	Panel with LED backlight	Digital Signage(Stand alone)
	Capacitive touch	SV + AV + AV_Looping	High brightness panel	Networking Digital Signage
	SAW touch	SV + AV + TV	Wide Temperature	Motion Sensor
	Infrared touch		Sunlight Readable	Light Sensor
	Protected glass			Auto-Dimming